

2 1/2" (64 MM) MIN.

DRYVIT DEMANDIT® SMOOTH OR COLOR PRIME™ ON SURFACES TO RECEIVE APPROVED TREMCO CPG SEALANT OR APPROVED EQUIVALENT

DRYVIT REINFORCING MESH MUST BE FULLY EMBEDDED IN DRYVIT BASE COAT AT EPS EDGE AND MUST EXTEND 2 1/2" (64 MM) MIN. BEYOND STEEL FRAME EDGE

LIGHT GAUGE STEEL FRAMING (SEE NOTE 2)

APPROVED SUBSTRATE

DRYVIT APPROVED INSULATION BOARD

DRYVIT APPROVED ADHESIVE IN VERTICAL NOTCHED TROWEL CONFIGURATION APPLIED TO BACK OF EPS

DRYVIT BASE COAT

DRYVIT REINFORCING MESH EMBEDDED IN DRYVIT BASE COAT (SEE NOTE 1 AND DETAIL OSL - 02)

DRYVIT BASE COAT

DRYVIT FINISH



APPROVED DRYVIT/TREMCO AIR/WATER-RESISTIVE BARRIER COATING AND FLASHING MATERIAL (SEE NOTE 3)

NOTES:

1. DRYVIT RECOMMENDS THAT GROUND FLOOR APPLICATIONS AND ALL FACADES EXPOSED TO ABNORMAL STRESS, HIGH TRAFFIC, OR DELIBERATE IMPACT HAVE THE BASE COAT REINFORCED WITH PANZER® MESH PRIOR TO STANDARD OR STANDARD PLUS MESH. LOCATION OF HIGH IMPACT ZONES SHOULD BE INDICATED ON CONTRACT DRAWINGS.
2. LIGHT GAUGE STEEL FRAME SHALL BE DESIGNED FOR SPECIFIC PROJECT LOADS AND CONDITIONS TO MEET LOCAL BUILDING CODES BY LICENSED ENGINEER.
3. REFER TO APPLICATION INSTRUCTIONS FOR THE APPROVED TREMCO CPG AIR BARRIER SYSTEM SELECTED FOR AWRB AND FLASHING APPLICATION.

This detail is for general informational purposes, only. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project with respect to any architecture, engineering, and design requirements, including any local building code requirements. If this document is not reviewed and the product is not approved for use by a licensed design professional, the customer agrees that the detail may contain substantive flaws requiring correction, and hereby releases Tremco CPG Inc. from any and all liability related to the design and installation of the product. This detail is subject to change without notice. Contact Tremco to ensure you have the most recent version.

Outsulite™ Panel System

 <p>Dryvit Technical Support: 800-556-7752</p>	Detail: Outsulite Panel System - Weep System Drainage Option			File Name:	 <p>Construction Products Group</p>
	Drawn by: EM	Checked by: CW	Scale: NTS	OSL 1MD	
	Revision #: 0	Revised by: NA	Date: 6/27/2024		
<p><small>www.tremcocpg.com</small></p>					