



NOTES:

1. DRYVIT RECOMMENDS THAT GROUND FLOOR APPLICATIONS AND ALL FACADES EXPOSED TO ABNORMAL STRESS, HIGH TRAFFIC, OR DELIBERATE IMPACT HAVE THE BASE COAT REINFORCED WITH PANZER® MESH PRIOR TO STANDARD OR STANDARD PLUS MESH. LOCATION OF HIGH IMPACT ZONES SHOULD BE INDICATED ON CONTRACT DRAWINGS.
2. LIGHT GAUGE STEEL FRAME SHALL BE DESIGNED FOR SPECIFIC PROJECT LOADS AND CONDITIONS TO MEET LOCAL BUILDING CODES BY LICENSED ENGINEER.
3. REFER TO APPLICATION INSTRUCTIONS FOR THE APPROVED TREMCO CPG AIR BARRIER SYSTEM SELECTED FOR AWRB AND FLASHING APPLICATION.
4. PANEL TO SLAB ATTACHMENT OPTION OR AS PER APPROVED ENGINEERED SHOP DRAWINGS. REFER TO PUBLICATION DS928 FOR OUTSULITE PANEL SYSTEM TYPICAL CONNECTION DETAILS.
5. TERMINATION OF THE OUTSULITE PANEL SYSTEM TO BE 6" (152 MM) MINIMUM ABOVE GRADE.

This detail is for general informational purposes only. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project with respect to any architecture, engineering, and design requirements, including any local building code requirements. If this document is not reviewed and the product is not approved for use by a licensed design professional, the customer agrees that the detail may contain substantive flaws requiring correction, and hereby releases Tremco CPG Inc. from any and all liability related to the design and installation of the product. This detail is subject to change without notice. Contact Tremco to ensure you have the most recent version.

Outsulite™ Panel System

| | | | | | |
|--|--------------------------------------|----------------|--|------------|--|
|  Dryvit Technical Support: 800-556-7752 | Detail: Termination at Slab on Grade | | | File Name: | |
| | Drawn by: EM | Checked by: CW | Scale: NTS | OSL 8 | |
| | Revision #: 0 | Revised by: NA | Date: 6/27/2024 | | |
| www.tremcocpg.com | | |  Construction Products Group | | |