



- FRAMING
- CODE AND DRYVIT APPROVED SHEATHING
- DRYVIT BACKSTOP® NT™ OR OTHER CODE APPROVED WATER-RESISTIVE BARRIER (NOTE 1)
- DRYVIT MD SPACERS™ OR EQUIVALENT
- CEMENT BOARD MEETING ASTM C1325 (OFFSET JOINTS FROM SHEATHING JOINTS)
- DRYVIT STANDARD REINFORCING MESH EMBEDDED IN DRYVIT GENESIS®, GENESIS® DM OR GENESIS® DMS BASE COAT
- DRYVIT FLASHING TAPE™ (NOTE 2)
- CASING BEAD
- 1/2" (12.7 MM) MIN. SEALANT JOINT WITH CLOSED CELL BACKER ROD AND SEALANT
- DRYVIT FINISH
- SILL PAN FLASHING WITH END DAMS
- SEALANT
- CASING BEAD
- DRYVIT MD SPACERS OR EQUIVALENT

## Cement Board MD Finish System™ Storefront Window Sill/Jamb

**NOTE:**

- 1: SHEET TYPE WATER-RESISTIVE MEMBRANES SHALL BE INSTALLED IN A WEATHER BOARD FASHION
- 2: DRYVIT AQUAFLASH® SYSTEM MAY BE USED IN LIEU OF DRYVIT FLASHING TAPE WHEN DRYVIT BACKSTOP NT IS USED AS THE WATER-RESISTIVE BARRIER

The architecture, engineering, and design of the project using the Dryvit products is the responsibility of the project's design professional. All systems must comply with local building codes and standards. This detail is for general information and guidance only and Dryvit specifically disclaims any liability for the use of this detail and for the architecture, design, engineering or workmanship of any project. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. Use of a functionally equivalent detail does not violate Dryvit's warranty. This detail is subject to change without notice. Contact Dryvit to ensure you have the most recent version.