



NOTE:

1. BACKSTOP® NTX AIR / WATER-RESISTIVE BARRIER REQUIRES USE OF A SLIP SHEET LAYER SUCH AS #15 FELT OR PAPER BACKED LATH WHEN SPECIFIED.
2. ADHESIVELY ATTACH EPS SHAPE TO CEMENT PLASTER BASE COAT WITH DRYVIT GENESIS® OR GENESIS® DM BASE COAT
3. OTHER APPROVED SCRATCH AND BROWN COATS MAY BE ACCEPTABLE. CONSULT DRYVIT FOR SPECIFICS.

The architecture, engineering, and design of the project using the Dryvit products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Dryvit specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Dryvit to ensure you have the most recent version.

Commercial Cement Plaster 4™

 Dryvit Technical Support: 800-556-7752	Detail: EPS Cornice			File Name:		 Construction Products Group
	Drawn by: KAB	Checked by:	Scale: NTS	Date: 5/2023	CCP-4 16	
www.tremcocpg.com						