

CODE APPROVED SHEATHING, BY OTHERS

PRESSURE TREATED WOOD STRAPPING OR EQUAL, BY OTHERS

DRYVIT BACKSTOP® NTX AIR / WATER-RESISTIVE BARRIER

BREATHER/BACKER BOARD, BY OTHERS

GALVANIZED SELF-FURRING LATH, BY OTHERS (SEE NOTE 2)

DRYVIT AQUAFLASH® SYSTEM

CONTINUOUS WINDOW PERIMETER STRAPPING, BY OTHERS

DRYVIT COMMERCIAL CEMENT PLASTER BASE™, (SEE NOTE 1) DRYVIT REINFORCING MESH EMBEDDED IN DRYVIT GENESIS® OR GENESIS® DM

DRYVIT PRIMER AND DRYVIT FINISH

MIN. 13 MM (1/2 IN) SEALANT JOINT WITH CLOSED CELL BACKER ROD, BY OTHERS

WINDOW BASE FLASHING WITH END DAMS, BY OTHERS

METAL ANGLE, BY OTHERS

INTERMITTENT SHIM, BY OTHERS

SEALANT, BY OTHERS

NOTE:

- OTHER APPROVED SCRATCH AND BROWN COATS MAY BE 1.
- ACCEPTABLE. CONSULT DRYVIT FOR SPECIFICS. 2 PAPER BACKED LATH OR OTHER SLIP SHEET MAY BE REQUIRED OVER CERTAIN SUBSTRATES.

The architecture, engineering, and design of the project using the Dryvit products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Dryvit specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Dryvit to ensure you have the most recent version.

Commercial Cement Plaster 5™

Scale: NTS

Checked by: KK



File Name: CCP-5 5



www.tremcocpg.com

Date: 4/2022