



- CODE APPROVED SHEATHING, BY OTHERS
- DRYVIT BACKSTOP® NTX AIR/WATER-RESISTIVE BARRIER
- BREATHER/BACKER BOARD, BY OTHERS
- GALVANIZED SELF FURRING LATH, BY OTHERS (SEE NOTE 2)
- PRESSURE TREATED WOOD STRAPPING OR EQUAL, BY OTHERS
- DRYVIT COMMERCIAL CEMENT PLASTER BASE™ (SEE NOTE 1)  
DRYVIT REINFORCING MESH EMBEDDED IN DRYVIT GENESIS® OR GENESIS® DM BASE COAT
- DRYVIT PRIMER AND FINISH
- MIN. 13 MM (1/2 IN) SEALANT JOINT WITH CLOSED CELL BACKER ROD, BY OTHERS
- INSECT SCREEN, BY OTHERS
- DRYVIT AQUAFASH® SYSTEM OVER VENT FLANGE
- DRYER VENT HOOD, SLOPED AT TOP, BY OTHERS

- NOTE:
1. OTHER APPROVED SCRATCH AND BROWN COATS MAY BE ACCEPTABLE. CONSULT DRYVIT FOR SPECIFICS.
  2. PAPER BACKED LATH OR OTHER SLIP SHEET MAY BE REQUIRED OVER CERTAIN SUBSTRATES.

*The architecture, engineering, and design of the project using the Dryvit products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Dryvit specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Dryvit to ensure you have the most recent version.*

**Commercial Cement Plaster 5™**

 Dryvit Technical Support: 800-556-7752	Detail: Termination at Dryer Vent				File Name:		 Construction Products Group
	Drawn by: KAB	Checked by: KK	Scale: NTS	Date: 4/2022	CCP-5 10		
www.tremcocpg.com							