



CLADDING (BY OTHERS)

FRAMING (BY OTHERS)

ACCEPTABLE SUBSTRATE (BY OTHERS)

DRYVIT STANDARD REINFORCING MESH EMBEDDED IN DRYVIT GENESIS® BASE COAT

COMPATIBLE SEALANT WITH BOND BREAKER OR BACKER ROD (BY OTHERS)

"L" BEAD (BY OTHERS)

DRYVIT FINISH

NOTE:

1. CONTROL JOINTS ARE RECOMMENDED EVERY 6.1 M (20 FT).
2. REFER TO DRYVIT PUBLICATION DS173 FOR SPECIFIC REQUIREMENTS FOR SOFFIT AREAS.

The architecture, engineering, and design of the project using the Dryvit products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Dryvit specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Dryvit to ensure you have the most recent version.

TAFS® 2 For Soffits



Dryvit Technical Support: 800-556-7752

Detail: Termination At Soffit - "L" Bead

Drawn by: KAB

Checked by: KK

Scale: NTS

Date: 5/2023

File Name:

TSS 2



Construction Products Group

www.tremcocpg.com