



- APPROVED SUBSTRATE
- DRYVIT AIR/WATER-RESISTIVE BARRIER COATING EXTENDED BEHIND FLASHING (SEE NOTE 3)
- DRYVIT ADHESIVE IN VERTICAL NOTCHED TROWEL CONFIGURATION APPLIED TO BACK OF EPS
- EPS INSULATION BOARD
- DRYVIT BASE COAT
- DRYVIT REINFORCING MESH EMBEDDED IN DRYVIT BASE COAT
- DRYVIT BASE COAT
- DRYVIT FINISH
- DRYVIT AQUAFLASH® SYSTEM (SEE NOTE 2)
- DRYVIT DETAIL MESH® WRAPPED TO BACKSIDE OF EPS MIN. 2 1/2" (64 MM)
- DRYVIT DRAINAGE STRIP™ ADHERED WITH DABS OF DRYVIT AP ADHESIVE
- 3/4" (19 MM) MIN.
- DRYVIT DEMANDIT® OR COLOR PRIME™ ON SURFACE(S) TO RECEIVE SEALANT
- DRYVIT COMPATIBLE SEALANT WITH CLOSED CELL BACKER ROD AND WEEP TUBES EVERY 24" (610 MM), BY OTHERS
- CONTINUOUS FLASHING, BY OTHERS
- SEALANT WITH BOND BREAKER, BY OTHERS
- PAPER BACKED EXPANDED METAL LATH OR OTHER SLIP SHEET, BY OTHERS
- STONE VENEER SYSTEM, BY OTHERS

## Outsulation® Plus MD System®

### Horizontal Termination at Stone Veneer

**NOTE:**

1. DRYVIT RECOMMENDS THAT GROUND FLOOR APPLICATIONS AND ALL FACADES EXPOSED TO ABNORMAL STRESS, HIGH TRAFFIC, OR DELIBERATE IMPACT HAVE THE BASE COAT REINFORCED WITH PANZER® MESH PRIOR TO STANDARD™ OR STANDARD PLUS™ MESH. LOCATION OF HIGH IMPACT ZONES SHOULD BE INDICATED ON CONTRACT DRAWINGS.

2. DRYVIT FLASHING TAPE SURFACE CONDITIONER™ AND DRYVIT FLASHING TAPE™ MAY BE USED IN LIEU OF DRYVIT AQUAFLASH SYSTEM.

3. FOR INSTALLATION OF DRYVIT AIR/WATER-RESISTIVE BARRIER COATING BENEATH CLADDINGS OTHER THAN DRYVIT EIFS, REFER TO DRYVIT PUBLICATION DS840.

The architecture, engineering, and design of the project using the Dryvit products is the responsibility of the project's design professional. All systems must comply with local building codes and standards. This detail is for general information and guidance only and Dryvit specifically disclaims any liability for the use of this detail and for the architecture, design, engineering or workmanship of any project. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. Use of a functionally equivalent detail does not violate Dryvit's warranty. This detail is subject to change without notice. Contact Dryvit to ensure you have the most recent version.

