

Table of Contents

Detail

OUTSULATION® PLUS MD SYSTEM*

OVER 1/2" GYPSUM, DENSGLOSS GOLD, SECUROCK OR E2XP (30 FEET OR LESS)	NOA 22-0914.14
OVER 5/8" DENSGLOSS GOLD, SECUROCK OR E2XP (30 FEET OR LESS)	NOA 22-0914.13
OVER ASTM C 1177 SHEATHING (ABOVE 30 FEET)	NOA 22-0914.15
OVER 5/8" E2XP (30 FEET OR LESS)	NOA 22-0914.16
OVER 5/8" E2XP (30 FEET OR LESS)	NOA 22-0914.17
OVER CONCRETE OR CONCRETE BLOCK	NOA 22-0914.12
OVER ASTM C 1177 SHEATHING	NOA 22-0914.09
OVER PLYWOOD	NOA 22-0914.11

OUTSULATION® SYSTEM

OVER ASTM C 1177 SHEATHING (ABOVE 30 FEET)	NOA 22-0914.15
OVER 5/8" E2XP (30 FEET OR LESS)	NOA 22-0914.16
OVER 5/8" E2XP (30 FEET OR LESS)	NOA 22-0914.17
OVER CONCRETE OR CONCRETE BLOCK	NOA 22-0914.12
OVER ASTM C 1177 SHEATHING	NOA 22-0914.09

OUTSULATION® X SYSTEM

OVER 5/8" ASTM C 1177 SHEATHING	NOA 22-0914.10
---------------------------------	----------------

NOTE:

DRYVIT AND TREMCO MAKES NO REPRESENTATION REGARDING CONFORMITY OF ITS SUGGESTIONS TO MODEL BUILDING CODES, ENGINEERING CRITERIA, SPECIFIC APPLICATIONS, OR PROJECT LOCATIONS. ALL COMPONENTS INDICATED IN ILLUSTRATIONS, AS WELL AS OTHERS THAT MAY BE REQUIRED FOR THE INTEGRITY OF THE SYSTEM SHALL BE DESIGNED, DETAILED, AND ENGINEERED BY REPRESENTATIVES OF THE ARCHITECT, OWNER, OR CONTRACTOR TO BE IN CONFORMANCE WITH MODEL CODES, ARCHITECTURAL, AND ENGINEERING REQUIREMENTS PERTAINING TO SPECIFIC BUILDING PROJECTS.

DRYVIT AND TREMCO MAKE NO WARRANTY, EXPRESSED OR IMPLIED, AS TO THE ARCHITECTURAL DESIGN, ENGINEERING, OR WORKMANSHIP OF PROJECTS UTILIZING DRYVIT SYSTEMS OR PRODUCTS.

THE LIABILITIES OF DRYVIT AND TREMCO SHALL BE AS STATED IN THE DRYVIT STANDARD WARRANTY. CONTACT DRYVIT AND TREMCO FOR A FULL AND COMPLETE COPY OF THE WARRANTY.

The architecture, engineering, and design of the project using the Dryvit and Tremco products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Dryvit and Tremco specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Dryvit and Tremco to ensure you have the most recent version.

Dryvit Outsulation® Systems



Dryvit Technical Support: 800-556-7752

Detail: Table of Contents

Drawn by: KAB

Checked by: KK

Scale: NTS

Date: 4/2023

File Name:

OS NOA TOC



Construction Products Group

www.tremcoopg.com