



TECHNICAL DATA SHEET

Expansion Joints/ Tremco Sealants

DS920

PRODUCT DESCRIPTION

The sizing of expansion joints and selection of sealants for use in weatherproofing of buildings utilizing Dryvit® systems and products is the responsibility of the project architect and/or engineer. Dryvit details addressing joints represent typical and/or general conditions and are presented in good faith by Dryvit. Dryvit assumes no responsibility for joint design or selection of sealant.

The following have been tested and have been found to be compatible with Dryvit products:

Sealant: Spectrem® 1, Spectrem 3, Spectrem 4 and Dymonic® FC

Primer: TREMprime® Silicone Porous Primer*

*Primer is for sealing Dryvit to Dryvit. For sealing Dryvit to other materials, consult with Tremco Technical Services at 866.209.2404 or Techresources@tremcoinc.com

INSTALLATION

1. Use skilled mechanics for installation of sealant system.
2. Follow Tremco Construction Products Group installation instructions.
3. Use fresh sealant materials that have arrived at the job site in their original unopened containers.
4. Inspect joint for proper design in accordance with contract documents, Dryvit. published details, and Tremco Construction Products Group recommendations, regarding width, depth, location, substrate, primer, etc. Report discrepancies to architect and correct deficiencies prior to installation of sealant system.
5. Make sure all joints are clean and free of all foreign matter such as moisture, frost, dust, sealers, release agents, paints, etc. before installation of sealant system.
6. Install sealant system only when climate conditions (temperature, humidity, etc.) meet Tremco Construction Products Group recommendations.
7. Protect adjacent materials, including Dryvit system, from damage during installation of sealant system. Mask adjacent areas as required.
8. Allow Dryvit system materials to cure prior to sealant application.
9. Apply a coat of color coordinated Dryvit Demandit® Smooth or Color Prime™ into the joint. Allow at least 24 hours to dry before application of the sealant primer. Do not return Dryvit finish into the sealant joint.
10. Install primer, bond breaker and backer rod as specified. Allow primer to cure. Remove primer overspill.
11. Mix sealant per Tremco Construction Products Group instructions.
12. Apply sealant with gun or knife as appropriate, using proper nozzle and technique. Sealant should completely fill joint cavity to backer material and be in intimate contact with substrate.
13. Tool surface of bead after sealant application, as to leave a neat-appearing, smooth, wrinkle-and-sag-free surface without—pockets or imbedded impurities, smears or width variations and in total contact with joint sides.
14. Remove sealant from all soiled surfaces.
15. Protect sealant from damage during curing.
16. Use closed cell material for back-up rods.


INSTALLATION CAUTIONS AND LIMITATIONS

Prior to applying sealant, ensure that the base coat is the cementitious type; Dryvit NCB is not recommended to embed reinforcing mesh at EPS edges that will receive sealant.

Notes

- Demandit Smooth or Color Prime will be applied into the joints prior to applying finish to the face of the wall.
- Demandit Smooth will be color matched to the finish and will be extended onto the face of the wall.
- If the sealant is recessed, the finish must be brought to the face of the sealant.
- Sealant must cover all transitions between the finish coat and Demandit Smooth.

The sizing of expansion joints and selection of sealants for use in weatherproofing of buildings utilizing Dryvit systems and products is the responsibility of the project architect and/or engineer. Dryvit details addressing joints represent typical and/or general conditions and are presented in good faith by Dryvit. Dryvit assumes no responsibility for joint design or selection of sealant.



Information contained in this product sheet conforms to the standard detail recommendations and specifications for the installation of Dryvit products as of the date of publication of this document and is presented in good faith. Dryvit assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To ensure that you are using the latest, most complete information, contact Dryvit.

For more information on Dryvit or Continuous Insulation, [click here](#).

Printed in USA. Issued 1.1.2022

©Dryvit 2022

DS920

Tremco Construction Products Group (CPG) brings together the Commercial Sealants & Waterproofing and Roofing & Building Maintenance divisions of Tremco CPG Inc.; Dryvit and Willseal brands; Nudura Inc.; Prebuck LLC; Tremco Barrier Solutions, Inc.; Weatherproofing Technologies, Inc.; Weatherproofing Technologies Canada, Inc.; and Pure Air Control Services, Inc.



dryvit.com | 800.556.7752



Construction Products Group

3735 Green Rd. | Beachwood, OH 44122
800.321.7906 | tremcocpg.com