



BLOCKING, SECURED TO FRAMING

DRYVIT/TREMCO APPROVED SEALANT WITH BOND BREAKER TAPE (SEE NOTES 2, 3)

NON-CORROSIVE PIPE SLEEVE SET IN SEALANT

NEOPRENE WASHER

SCREW/BOLT ATTACHMENT TO BUILDING FRAMING/BLOCKING

- NOTE:
1. DRYVIT RECOMMENDS THAT GROUND FLOOR APPLICATIONS AND ALL FACADES EXPOSED TO ABNORMAL STRESS, HIGH TRAFFIC, OR DELIBERATE IMPACT HAVE THE BASE COAT REINFORCED WITH PANZER® MESH PRIOR TO STANDARD OR STANDARD PLUS MESH. LOCATION OF HIGH IMPACT ZONES SHOULD BE INDICATED ON CONTRACT DRAWINGS.
  2. REFERENCE DS920 FOR APPROVED SEALANTS.

3. APPLY DYMONIC 100 AT 40 MILS 1" (25 MM) MIN. ONTO FACE OF SECUROCK EXOAIR 430 PANEL AND 1-5/8" (41 MM) MIN. ONTO OUTSULITE PANEL EDGE.



*The architecture, engineering, and design of the project using the Dryvit Tremco and USG products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Dryvit Tremco and USG specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Dryvit Tremco and USG to ensure you have the most recent version.*

**Outsulite® Securock® ExoAir® 430 Panel System**

<p>SECUROCK® EXOAIR® 430</p> <p>Technical Support: 866-209-2404</p>	Detail: Fastener through System			File Name:	<p>Construction Products Group</p>
	Drawn by: HDE	Checked by:	Scale: NTS	Date: 1/9/2023	
www.tremcocpg.com					