



TECHNICAL DATA SHEET

COLOR MIST™

Pigmented Acrylic for Dryvit Finishes
DS482

Description

Color Mist is a water-based, pigmented acrylic which provides a flat, non-slip, uniformly absorbent, color coordinated surface for application of Dryvit exterior and interior finishes. Color Mist is available in a variety of standard colors as well as custom colors.

Uses

Color Mist is recommended for the surface application over Dryvit acrylic finishes to create a decorative flat coating where desired.

Coverage

Approximately 1500 ft² (140 m²) per 50 lb (23 kg) pail, depending upon surface roughness and porosity of the substrate.

Properties

Drying Time – The drying time of Color Mist is dependent upon the air temperature and relative humidity. Under average drying conditions [70°F (21°C), 55% R. H.], Color Mist is dry to the touch in 1/2 hour. Protect from rain for at least 4 hours.

Application Procedure

Job Conditions – Temperature for application of Color Mist must be 40°F (4°C) or higher and must remain so for a minimum of 24 hours.

Surface Preparation - Surfaces shall not be below 40°F (4°C) and must be clean, dry, structurally sound, and free of efflorescence, grease, oil, form release agents and curing compounds. On painted surfaces, remove all blistered or peeling paint to a sound substrate. Remove all gloss by sanding.

Mixing – Stir to a smooth, homogeneous consistency.

Application – Color Mist can be applied using a brush or paint roller but is designed for spray equipment.

Clean Up – Clean tools with water while Color Mist is still wet.

Storage

Color Mist must be stored at 40°F (4°C) or above in tightly sealed containers out of direct sunlight.

Technical and Field Services

Available on request.

Information contained in this product sheet conforms to the standard detail recommendations and specifications for the installation of Dryvit products as of the date of publication of this document and is presented in good faith. Dryvit assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To ensure that you are using the latest, most complete information, contact Dryvit.

For more information on Dryvit or Continuous Insulation, [click here](#).

Printed in USA. Issued 1.1.2022
©Dryvit 2022

February 2022/DS482

Tremco Construction Products Group (CPG) brings together the Commercial Sealants & Waterproofing and Roofing & Building Maintenance divisions of Tremco CPG Inc.; Dryvit and Willseal brands; Nudura Inc.; Prebuck LLC; Tremco Barrier Solutions, Inc.; Weatherproofing Technologies, Inc.; Weatherproofing Technologies Canada, Inc.; and Pure Air Control Services, Inc.



dryvit.com | 800.556.7752



Construction Products Group

3735 Green Rd. | Beachwood, OH 44122
800.321.7906 | tremcocpg.com