

# Table of Contents

## Detail

|   |         |
|---|---------|
| OUTSULATION MINERAL WOOL SYSTEM CUTAWAY                                       | OMW 1   |
| AWRB APPLICATION  | OMW 2   |
| OPENING PREPARATION- AQUAFLASH® SYSTEM OR EXOAIR 230 WITH MESH OPTION         | OMW 3   |
| OPENING PREPARATION- BACKSTOP® FLASH AND FILL OR DYMONIC 100 OPTION           | OMW 3a  |
| OPENING PREPARATION- BACKSTOP® NTX OR EXOAIR 230 WITH MESH OPTION             | OMW 4   |
| OPENING FLASHING INTEGRATION  | OMW 5   |
| OPENING FLASHING INTEGRATION - BACKSTOP® FLASH AND FILL OR DYMONIC 100 OPTION | OMW 5a  |
| MECHANICAL FASTENINGS - 6 AND 9 FASTENER PATTERN                              | OMW 6   |
| MECHANICAL FASTENINGS - 5 FASTENER PATTERN AND LOAD TABLES                    | OMW 6a  |
| FASTENER OPTIONS  | OMW 7   |
| STARTER BOARD   | OMW 8   |
| INSIDE/OUTSIDE CORNERS  | OMW 9   |
| INSIDE/OUTSIDE CORNERS - BACKSTOP® FLASH AND FILL OR DYMONIC 100 OPTION       | OMW 9a  |
| OUTSIDE CORNER - HIGH IMPACT  | OMW 10  |
| TERMINATION AT GRADE  | OMW 11  |
| TERMINATION AT CONCRETE CURB  | OMW 12  |
| TERMINATION AT ADA COMPLIANT SIDEWALK   | OMW 13  |
| TERMINATION AT ADA COMPLIANT SIDEWALK - TREMCO OPTION                         | OMW 13a |
| TERMINATION AT WATERPROOF DECK  | OMW 14  |
| TERMINATION AT WOOD FRAMED DECK   | OMW 15  |

## Detail

|   |         |
|---|---------|
| INSULATION PREPARATION AT WALL PENETRATIONS                     | OMW 16  |
| STOREFRONT WINDOW SILL - JAMB                                   | OMW 17  |
| STOREFRONT AND FLANGED WINDOW HEAD                              | OMW 18  |
| PREPARATION AT PARAPET/ WALL INTERSECTION                       | OMW 19  |
| TERMINATION AT PARAPET - CAP FLASHING                           | OMW 20  |
| TERMINATION AT ROOF MEMBRANE                                    | OMW 21  |
| TERMINATION AT ROOF MEMBRANE - EXOAIR 110AT/DYMONIC 100 OPTION  | OMW 21a |
| TERMINATION AT SLOPED ROOF                                      | OMW 22  |
| VERTICAL WALL/SUSPENDED SOFFIT TRANSITION                       | OMW 23  |
| TRANSITION AT SOFFIT/ FASCIA INTERSECTION                       | OMW 24  |
| FASCIA/UNINSULATED SOFFIT TRANSITION                            | OMW 25  |
| TERMINATION AT UNINSULATED SOFFIT VENT                          | OMW 26  |
| HORIZONTAL JOINT AT FLOOR LINE WITHOUT WEEPS                    | OMW 27  |
| HORIZONTAL JOINT AT FLOOR LINE WITH WEEPS                       | OMW 28  |
| HORIZONTAL JOINT AT FLOOR LINE WITH WEEPS - DYMONIC SIMPLE SEAL | OMW 28a |
| HORIZONTAL JOINT - SUBSTRATE CHANGE                             | OMW 29  |
| HORIZONTAL TERMINATION AT STONE VENEER                          | OMW 30  |
| HORIZONTAL TERMINATION AT STUCCO                                | OMW 31  |
| HORIZONTAL TERMINATION AT LAPPED SIDING                         | OMW 32  |
| VERTICAL EIFS EXPANSION JOINT                                   | OMW 33  |
| THROUGH-WALL EXPANSION JOINT                                    | OMW 34  |
| THROUGH-WALL EXPANSION JOINT - DYMONIC SIMPLE SEAL OPTION       | OMW 34a |
| VERTICAL EXPANSION JOINT - FLUSH AND RECESSED OPTIONS           | OMW 35  |
| VERTICAL EXPANSION JOINT - DOUBLE SEAL OPTION                   | OMW 36  |
| VERTICAL TERMINATION AT STONE VENEER                            | OMW 37  |
| PENETRATIONS  | OMW 38  |
| SIGN ATTACHMENT   | OMW 39  |
| AESTHETIC REVEALS   | OMW 40  |
| EPS SHAPES  | OMW 41  |

**NOTE:**

DRYVIT AND TREMCO MAKES NO REPRESENTATION REGARDING CONFORMITY OF ITS SUGGESTIONS TO MODEL BUILDING CODES, ENGINEERING CRITERIA, SPECIFIC APPLICATIONS, OR PROJECT LOCATIONS. ALL COMPONENTS INDICATED IN ILLUSTRATIONS, AS WELL AS OTHERS THAT MAY BE REQUIRED FOR THE INTEGRITY OF THE SYSTEM SHALL BE DESIGNED, DETAILED, AND ENGINEERED BY REPRESENTATIVES OF THE ARCHITECT, OWNER, OR CONTRACTOR TO BE IN CONFORMANCE WITH MODEL CODES, ARCHITECTURAL, AND ENGINEERING REQUIREMENTS PERTAINING TO SPECIFIC BUILDING PROJECTS.

DRYVIT AND TREMCO MAKE NO WARRANTY, EXPRESSED OR IMPLIED, AS TO THE ARCHITECTURAL DESIGN, ENGINEERING, OR WORKMANSHIP OF PROJECTS UTILIZING DRYVIT SYSTEMS OR PRODUCTS.

THE LIABILITIES OF DRYVIT AND TREMCO SHALL BE AS STATED IN THE DRYVIT STANDARD WARRANTY. CONTACT DRYVIT AND TREMCO FOR A FULL AND COMPLETE COPY OF THE WARRANTY.

*The architecture, engineering, and design of the project using the Dryvit and Tremco products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Dryvit and Tremco specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Dryvit and Tremco to ensure you have the most recent version.*



Dryvit Technical Support: 800-556-7752

Detail: Table of Contents

Drawn by: HDE

Checked by: KK  
BD

Scale: NTS

Date: 11/2022

File Name:

TOC

