



- NOTE:**
- REFER TO PRODUCT DATA SHEETS FOR SPECIFIC APPLICATION METHODS.
  - WALL ASSEMBLY SHALL PROVIDE FOR A MAXIMUM DESIGN DEFLECTION OF L/360.
  - OPTIONAL CONTINUOUS INSULATION BOARD HAVE MINIMUM 1/4" WIDE x 1/8" DEEP GROOVES SPACED 12" ON CENTER. GROOVES SHALL BE ORIENTATED VERTICALLY WHEN INSTALLED. JOINTS SHALL BE 1/8" OR LESS AND CLOSED ON THE EXTERIOR SIDE USING MINIMUM 2 3/8" WIDE FIBERGLASS MESH TAPE.

*The architecture, engineering, and design of the project using the Dryvit and Tremco products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Dryvit and Tremco specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Dryvit and Tremco to ensure you have the most recent version.*

**StucCoat One Coat® System**

 Dryvit Technical Support: 800-556-7752	Detail: Outside Corner			File Name:		 Construction Products Group
	Drawn by: KAB	Checked by: BD/CB	Scale: NTS	Date: 4/2023	SCOC CI 13	
www.tremcocpg.com						