



**NOTE:**

1. REFER TO PRODUCT DATA SHEETS FOR SPECIFIC APPLICATION METHODS.
2. WALL ASSEMBLY SHALL PROVIDE FOR A MAXIMUM DESIGN DEFLECTION OF L/360.
3. DYMONIC 100 MUST NOT BE LEFT EXPOSED TO U.V.

*The architecture, engineering, and design of the project using the Dryvit, Tremco and USG products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Dryvit, Tremco and USG specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Dryvit, Tremco and USG to ensure you have the most recent version.*



Dryvit Technical Support: 800-556-7752

**StucCoat One Coat® Securock® ExoAir 430 System**

**USG** | **TREMCO**  
**SECUROCK® EXOAIR® 430**  
 Technical Support: 866-209-2404

Detail: Horizontal Flashing & Expansion Joint				File Name:
Drawn by: KAB	Checked by: BD/CB	Scale: NTS	Date: 4/2023	SCOC SE430 15
www.tremcocpg.com				

**TREMCO**  
 Construction Products Group