

APPROVED FRAMING, BY OTHERS
(SEE NOTE 2)

DRYVIT PRIMER,
AS SPECIFIED OR
REQUIRED

WEATHERLASTIC® FINISH

STUCCOAT CRACK
ISOLATION MEMBRANE

2" (51 MM) MIN.

TREMCO CPG SEALANT
OR EQUIVALENT, BY
OTHERS
(SEE NOTE 3)

END JOIST

DECK BOARD

FLASHING NO. 1,
BY OTHERS

APPROVED TREMCO CPG SEALANT OR
APPROVED EQUIVALENT, BY
OTHERS(SEE NOTE 3)

STANDARD REINFORCING MESH

STUCCOAT ONE COAT BASE,
3/8" MIN.

METAL PLASTER BASE AS
SPECIFIED, BY OTHERS

PAPER BACKING, BY OTHERS

SECUROCK® EXOAIR® 430

TREMCO DYMONIC® 100 OR
TREMCO EXOAIR® 110AT WITH
DYMONIC 100 TERMINATION BEAD
(SEE NOTE 1)

CASING BEAD WITH WEEP
HOLES, BY OTHERS

2" (51 MM) MIN.

FLASHING NO. 3, BY OTHERS

FLASHING NO. 2, BY OTHERS

1" (25 MM) MIN.

2-1/2"(64 MM) MIN.

NOTE:

1. REFER TO PRODUCT DATA SHEETS FOR SPECIFIC APPLICATION METHODS.

2. WALL ASSEMBLY SHALL PROVIDE FOR A MAXIMUM DESIGN DEFLECTION OF L/360.

3. BACKER ROD AND SEALANT JOINT SHALL NOT COVER OR OBSTRUCT CASING BEAD WEEP HOLES.

4. DETAIL DOES NOT APPLY TO CANTILEVERED DECKS. CANTILEVERED DECKS REQUIRE JOB SPECIFIC FLASHING DETAILS.

The architecture, engineering, and design of the project using the Dryvit, Tremco and USG products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Dryvit, Tremco and USG specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Dryvit, Tremco and USG to ensure you have the most recent version.



Dryvit Technical Support: 800-556-7752

StucCoat One Coat® Securock® ExoAir 430 System



Technical Support: 866-209-2404

Detail: Termination at Wood Framed Deck

Drawn by: KAB

Checked by: BD/CB

Scale: NTS

Date: 4/2023

File Name:

SCOC SE430 16



www.tremcocpg.com