

PRIMER WITH SAND™

DSC477

Acrylic-Based Primer with Sand

Description

Primer with Sand is a pigmented water-based acrylic primer containing fine sand that can be applied over a variety of substrates. Fine sand content develops a uniform light textured surface that imparts grip and facilitates subsequent trowel application of Dryvit® textured finishes. This greatly reduces the potential for balded areas that may occur when finishes are troweled over smooth, sealed surfaces.

Uses

- Interior applications where finish is applied over drywall.
- On stucco when a Dryvit textured finish will be troweled over the stucco brown or finish coat. The primed surface is more uniform, producing superior uniform finish appearance.
- Under certain Accent color textured finishes. Should be tinted to a color similar to color of the Accent color finish.
- Prior to application of fine sand textured finishes.
- Whenever a primer is used prior to trowel application of Sandblast® finish.

Coverage

Varies according to the texture and porosity of the substrate on which it is applied and application technique used. Coverage is usually in the range of 46-65 m² (500-700 ft²) per pail. The best way to accurately estimate coverage is to test a pre-measured area using the substrate type and application methods for the job in question.

Properties

Drying Time – Will vary according to temperature, humidity, and porosity of surface coated. Under average conditions [21 °C (70 °F), 55% R.H. Primer with Sand dries to the touch in 1 hour, and is sufficiently dry for application of finish in 3-4 hours. Protect from rain for at least four hours.

Application Procedure

Job Conditions - Air and surface temperature for application of Primer With Sand must be 4 °C (40 °F) or higher and must remain so for a minimum of 24 hours.

Temporary Protection - Shall be provided at all times until the base coat, finish and permanent flashings, sealants, etc. are completed to protect the wall from weather and other damage.

Surface Preparation - Surfaces shall not be below 4 °C (40 °F) and must be clean, dry, structurally sound and free of efflorescence, grease, oil, form release agents and curing compounds. On painted surfaces, remove all blistered or peeling paint to a sound substrate. Remove all gloss by sanding.

Mixing –Stir to a smooth, homogeneous consistency or mix with a slow-speed (500 RPM or less) mixer prior to application.

Application – A roller is recommended for application of Primer with Sand. Sufficient material should be used to uniformly coat the substrate

without runs or buildup of material. Maintain a wet edge and work to a logical wall break to minimize lap marks. Backroll the wet application immediately with all strokes downward. Product may also be applied over small areas using a brush. Brush application is difficult to apply uniformly on large areas. Spray application must be done with air assisted airless or other type of spray equipment that will not be damaged by the fine sand content.

Clean Up - Clean tools with water while Primer With Sand is still wet.

Storage

Primer With Sand must be stored at 4 °C (40 °F) or above in tightly sealed containers out of direct sunlight.

Limitations

Not for use on horizontal, traffic-bearing surfaces.

Technical and Field Services

Available upon request.

Dryvit Systems Canada
129 Ringwood Drive
Stouffville, Ontario
Canada L4A 8A2
(800)-263-3308
www.dryvit.com

This information conforms to the standard detail recommendations and specifications for the installation of Dryvit Systems Canada products as of the date of publication of this document and is presented in good faith. Dryvit Systems Canada assumes no liability, expressed or implied, as to the architecture, engineering or workmanship of any project. To ensure that you are using the latest, most complete information, contact Dryvit Systems Canada .

