



- FRAMING, BY OTHERS
- APPROVED SUBSTRATE, BY OTHERS
- FEDDERLITE APPROVED PANEL ADHESIVE
- DRYVIT BASE COAT WITH EMBEDDED DRYVIT REINFORCING MESH
- 2" (50 MM) MIN. THICKNESS EXPANDED POLYSTYRENE INSULATION BOARD
- DRYVIT BASE COAT AND REINFORCING MESH WRAPPED TO BACKSIDE OF INSULATION BOARD 2-1/2" (64 MM)
- DRYVIT/TREMCO APPROVED FLASHING MATERIAL (SEE NOTE 3)
- APPROVED TREMCO CPG SEALANT OR APPROVED EQUIVALENT WITH CLOSED CELL BACKER ROD, BY OTHERS
- DRYVIT DEMANDIT® SMOOTH OR COLOR PRIME™ ON SURFACES TO RECEIVE SEALANT
- DRYVIT/TREMCO AIR/WATER-RESISTIVE BARRIER COATING (SEE NOTE 3)
- FEDDERLITE CHANNEL, SPACING AS PER APPROVED SHOP DRAWINGS
- MOUNTING PLATE OPTION (SEE NOTE 4)
- DRYVIT FINISH

NOTES:

1. DRYVIT RECOMMENDS THAT GROUND FLOOR APPLICATIONS AND ALL FACADES EXPOSED TO ABNORMAL STRESS, HIGH TRAFFIC, OR DELIBERATE IMPACT HAVE THE BASE COAT REINFORCED WITH PANZER® MESH PRIOR TO STANDARD OR STANDARD PLUS MESH. LOCATION OF HIGH IMPACT ZONES SHOULD BE INDICATED ON CONTRACT DRAWINGS.
2. LIGHT GAUGE STEEL FRAME SHALL BE DESIGNED FOR SPECIFIC PROJECT LOADS AND CONDITIONS TO MEET LOCAL BUILDING CODES BY LICENSED ENGINEER.
3. REFER TO DRYVIT PUBLICATION DS840 FOR AWRB AND FLASHING APPLICATION.
4. MOUNTING CLIP MAY BE USED AS AN ALTERNATE TO EXTENDING THE FEDDERLITE CHANNEL.

The architecture, engineering, and design of the project using the Dryvit and Tremco products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Dryvit and Tremco specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Dryvit or Tremco to ensure you have the most recent version.

Fedderlite® Panel System



Detail: Penetration

File Name:

Drawn by: HDE

Checked by: RB
CW

Scale: NTS

Date: 1/31/2024

FL 32



Dryvit Technical Support: 800-556-7752

www.tremcocpg.com