

Revision Date: 11/11/2022

SAFETY DATA SHEET

1. Identification

Material name: WEATHERLASTIC HB MASONRY PRIMER 5GL PL

Material: 555853B805

Recommended use and restriction on use

Recommended use: Coatings Restrictions on use: Not known.

Manufacturer/Importer/Supplier/Distributor Information

Tremco CPG Inc. - U.S. Sealants 3735 Green Road Beachwood OH 44122

US

Contact person:EH&S DepartmentTelephone:216-292-5000

Emergency telephone number: 1-800-424-9300 (US); 1-613-996-6666 (Canada)

2. Hazard(s) identification

Hazard Classification

Health Hazards

Carcinogenicity Category 1A

Unknown toxicity - Health

Acute toxicity, oral 44.26 %
Acute toxicity, dermal 46.8 %
Acute toxicity, inhalation, vapor 100 %
Acute toxicity, inhalation, dust 99.8 %

or mist

Environmental Hazards

Acute hazards to the aquatic Category 3 environment

Unknown toxicity - Environment

Acute hazards to the aquatic 78.05 %

environment

Chronic hazards to the aquatic 100 %

environment

Label Elements

Hazard Symbol:



Revision Date: 11/11/2022



Signal Word: Danger

Hazard Statement: May cause cancer.

Harmful to aquatic life.

Precautionary Statements

Prevention: Obtain special instructions before use. Do not handle until all safety

precautions have been read and understood. Use personal protective

equipment as required. Avoid release to the environment.

Response: IF exposed or concerned: Get medical advice/attention.

Storage: Store locked up.

Disposal: Dispose of contents/container to an appropriate treatment and disposal

facility in accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC):

None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Calcium carbonate	471-34-1	15 - 40%
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	15 - 40%
Barium sulfate	7727-43-7	10 - 30%
Propylene glycol	57-55-6	1 - 5%
Titanium dioxide	13463-67-7	1 - 5%
Cellulose	9004-34-6	0.5 - 1.5%
Magnesite	546-93-0	0.1 - 1%
Aluminum oxide	1344-28-1	0.1 - 1%
Clay	1332-58-7	0.1 - 1%

^{*} All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Description of necessary first-aid measures

Inhalation: Move to fresh air.

Skin Contact: Wash skin thoroughly with soap and water. Get medical attention if

symptoms occur.



Revision Date: 11/11/2022

Eye contact: Any material that contacts the eye should be washed out immediately

with water. If easy to do, remove contact lenses. If eye irritation

persists: Get medical advice/attention.

Ingestion: Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.

Personal Protection for First-

aid Responders:

Self-contained breathing apparatus and full protective clothing must

be worn in case of fire.

Most important symptoms/effects, acute and delayed

Symptoms: May cause skin and eye irritation.

Hazards: No data available.

Indication of immediate medical attention and special treatment needed

Treatment: Symptoms may be delayed.

5. Fire-fighting measures

General Fire Hazards: No unusual fire or explosion hazards noted.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing

media:

Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing

media:

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical:

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for fire-fighters

Special fire-fighting

procedures:

No data available.

Special protective equipment

for fire-fighters:

Self-contained breathing apparatus and full protective clothing must be

worn in case of fire.

6. Accidental release measures

Personal precautions,

protective equipment and emergency procedures:

No data available.

Accidental release measures: In the event of a spill or accidental release, notify relevant authorities in

accordance with all applicable regulations.



Revision Date: 11/11/2022

Methods and material for containment and cleaning

up:

Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for

disposal according to local regulations.

Environmental Precautions: Do not contaminate water sources or sewer. Prevent further leakage or

spillage if safe to do so. Avoid release to the environment.

7. Handling and storage

Handling

Technical measures (e.g. Local and general ventilation):

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical

ventilation or local exhaust ventilation may be required.

Safe handling advice: Do not handle until all safety precautions have been read and understood.

Obtain special instructions before use. Use personal protective equipment as required. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Contact avoidance measures: No data available.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and

immediately after handling the product.

Storage

Safe storage conditions: Store locked up.

Safe packaging materials: No data available.

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Туре	Exposure Limit Values	Source
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Calcium carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Calcium carbonate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (01 2017)
Calcium carbonate - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
Calcium carbonate - Inhalable particles.	TWA	10 mg/m3	US. ACGIH Threshold Limit Values, as amended (01 2021)
Calcium carbonate - Respirable particles.	TWA	3 mg/m3	US. ACGIH Threshold Limit Values, as amended (01 2021)
Calcium carbonate - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
Calcium carbonate - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)
	TWA	50 millions of particles per	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (09 2016)





Revision Date: 11/11/2022

		cubic foot of	
		air	
Calcium carbonate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (01 2017)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	0.05 mg/m3	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended (03 2016)
	OSHA_AC T	0.025 mg/m3	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053), as amended (03 2016)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	PEL	0.05 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (03 2016)
Crystalline Silica (Quartz)/ Silica Sand - Respirable.	TWA	2.4 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
	TWA	0.1 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (2000)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m3	US. ACGIH Threshold Limit Values, as amended (02 2020)
Barium sulfate - Inhalable fraction.	TWA	5 mg/m3	US. ACGIH Threshold Limit Values, as amended (02 2014)
Barium sulfate - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Barium sulfate - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Barium sulfate - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Barium sulfate - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Barium sulfate - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Titanium dioxide	TWA	10 mg/m3	US. ACGIH Threshold Limit Values, as amended (2008)
Titanium dioxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Titanium dioxide - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Titanium dioxide - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Titanium dioxide - Respirable fraction.	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Titanium dioxide - Total dust.	TWA	50 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Cellulose	TWA	10 mg/m3	US. ACGIH Threshold Limit Values, as amended (2011)
Cellulose - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Cellulose - Respirable fraction.	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000), as amended (02 2006)
Cellulose - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as



Revision Date: 11/11/2022

	1		
	TIA/A	50 W 5	amended (09 2016)
	TWA	50 millions of	US. OSHA Table Z-3 (29 CFR 1910.1000), as
		particles per	amended (09 2016)
		cubic foot of air	
Cellulose - Respirable	TWA	15 millions of	US. OSHA Table Z-3 (29 CFR 1910.1000), as
fraction.	1 1 1 1 1	particles per	amended (09 2016)
naodon.		cubic foot of	amonada (66 2616)
		air	
	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as
		og,e	amended (09 2016)
Magnesite - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air
			Contaminants (29 CFR 1910.1000), as
			amended (02 2006)
Magnesite - Respirable	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air
fraction.		3. 3.	Contaminants (29 CFR 1910.1000), as
			amended (02 2006)
Magnesite - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as
3		3. 3.	amended (09 2016)
Magnesite - Respirable	TWA	3 mg/m3	US. ACGIH Threshold Limit Values, as
particles.		55	amended (01 2021)
Magnesite - Total dust.	TWA	50 millions of	US. OSHA Table Z-3 (29 CFR 1910.1000), as
<u> </u>		particles per	amended (09 2016)
		cubic foot of	
		air	
Magnesite - Inhalable	TWA	10 mg/m3	US. ACGIH Threshold Limit Values, as
particles.		ŭ	amended (01 2021)
Magnesite - Respirable	TWA	15 millions of	US. OSHA Table Z-3 (29 CFR 1910.1000), as
fraction.		particles per	amended (09 2016)
		cubic foot of	,
		air	
	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as
		3. 3.	amended (09 2016)
Aluminum oxide - Respirable	TWA	1 mg/m3	US. ACGIH Threshold Limit Values, as
fraction.		ŭ	amended (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air
		ŭ	Contaminants (29 CFR 1910.1000), as
			amended (02 2006)
Aluminum oxide - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air
		-	Contaminants (29 CFR 1910.1000), as
			amended (02 2006)
	TWA	50 millions of	US. OSHA Table Z-3 (29 CFR 1910.1000), as
		particles per	amended (03 2016)
		cubic foot of	
		air	
Aluminum oxide - Respirable	TWA	15 millions of	US. OSHA Table Z-3 (29 CFR 1910.1000), as
fraction.		particles per	amended (03 2016)
		cubic foot of	·
		air	
	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as
			amended (03 2016)
Aluminum oxide - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as
		3	amended (03 2016)
Aluminum oxide - Inhalable	TWA	10 mg/m3	US. ACGIH Threshold Limit Values, as
particles.		~	amended (01 2021)
Aluminum oxide - Respirable	TWA	3 mg/m3	US. ACGIH Threshold Limit Values, as
particles.			amended (01 2021)
Clay - Respirable fraction.	TWA	2 mg/m3	US. ACGIH Threshold Limit Values, as
			amended (2011)
	PEL	5 mg/m3	US. OSHA Table Z-1 Limits for Air
		3	Contaminants (29 CFR 1910.1000), as
			amended (02 2006)
Clay - Total dust.	PEL	15 mg/m3	US. OSHA Table Z-1 Limits for Air
-		5	Contaminants (29 CFR 1910.1000), as
			amended (02 2006)
	TWA	50 millions of	US. OSHA Table Z-3 (29 CFR 1910.1000), as
	1		
		particles per	amended (03 2016)
		particles per cubic foot of	amended (03 2016)



Revision Date: 11/11/2022



Clay - Respirable fraction.	TWA	15 millions of particles per cubic foot of air	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
	TWA	5 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)
Clay - Total dust.	TWA	15 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000), as amended (03 2016)

Chemical name	Туре	Exposure Limit Values	Source
Calcium carbonate - Total dust.	STEL	20 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Calcium carbonate - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Calcium carbonate - Respirable fraction.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2020)



Revision Date: 11/11/2022

Calcium carbonate - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2020)
Calcium carbonate - Respirable particles.	TWA	3 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Calcium carbonate - Inhalable particles.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Calcium carbonate - Inhalable fraction.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (01 2020)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Crystalline Silica (Quartz)/ Silica Sand - Respirable dust.	TWA	0.1 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)
Crystalline Silica (Quartz)/ Silica Sand - Respirable fraction.	TWA	0.025 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (06 2020)
Barium sulfate - Inhalable fraction.	TWA	5 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (08 2017)
Barium sulfate - Inhalable	TWA	5 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2018)
Barium sulfate - Total dust.	TWA	5 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (03 2020)
Propylene glycol - Aerosol.	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Propylene glycol - Vapor and aerosol.	TWA	50 ppm 155 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (06 2015)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide - Respirable fraction.	TWA	3 mg/m3	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Biological Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Titanium dioxide	TWA	10 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents), as amended (11 2010)
Titanium dioxide - Total dust.	TWA	10 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety), as amended (09 2017)

Appropriate Engineering Controls

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.

Individual protection measures, such as personal protective equipment

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin Protection

Hand Protection: Additional Information: Use suitable protective gloves if risk of skin contact.



Revision Date: 11/11/2022

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: In case of inadequate ventilation use suitable respirator. Seek advice from

local supervisor.

Hygiene measures: Observe good industrial hygiene practices. Wash hands before breaks and

immediately after handling the product.

9. Physical and chemical properties

Appearance

Physical state: liquid
Form: liquid
Color: Off-white
Odor: Mild

Odor threshold: No data available.

pH: 9 - 10

Melting point/freezing point:
Initial boiling point and boiling range:
Flash Point:

Evaporation rate:

-0.00 °C 32 °F

No data available.

No data available.

Slower than Ether

Flammability (solid, gas):

Upper/lower limit on flammability or explosive limits

Flammability limit - upper (%):

Flammability limit - lower (%):

Explosive limit - upper:

Explosive limit - lower:

No data available.

No data available.

No data available.

No data available.

Vapor pressure:

No data available.

Vapor density: Vapors are heavier than air and may travel along the floor and

in the bottom of containers.

Relative density: 1.558

Solubility(ies)

Solubility in water: Soluble

Solubility (other): No data available.

Partition coefficient (n-octanol/water): No data available.

Auto-ignition temperature:No data available.Decomposition temperature:No data available.Viscosity:No data available.

10. Stability and reactivity

Reactivity: No data available.

Chemical Stability: Material is stable under normal conditions.



Revision Date: 11/11/2022

Possibility of hazardous

reactions:

No data available.

Conditions to avoid: Avoid heat or contamination.

Incompatible Materials: Strong acids. Strong bases.

Hazardous Decomposition

Products:

Thermal decomposition or combustion may liberate carbon oxides and

other toxic gases or vapors.

11. Toxicological information

Information on likely routes of exposure

In high concentrations, vapors, fumes or mists may irritate nose, throat and

mucus membranes.

Skin Contact: May be harmful in contact with skin.

Eye contact: Eye contact is possible and should be avoided.

Ingestion: May be ingested by accident. Ingestion may cause irritation and malaise.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation: No data available.

Skin Contact: No data available.

Eye contact: No data available.

Ingestion: No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product: Not classified for acute toxicity based on available data.



Revision Date: 11/11/2022

Specified substance(s):

Calcium carbonate LD 50 (Rat): > 2,000 mg/kg

Crystalline Silica

(Quartz)/ Silica Sand

LD 50: > 2,000 mg/kg

Barium sulfate LD 50 (Rat): 307 g/kg

Propylene glycol LD 50 (Rat): 22,000 mg/kg

Titanium dioxide LD 50 (Rat): > 5,000 mg/kg

Cellulose LD 50 (Rat): 5,001 mg/kg

Magnesite LD 50 (Rat): > 2,000 mg/kg

Aluminum oxide LD 50 (Rat): > 10,000 mg/kg

Clay LD 50 (Rat): > 5,000 mg/kg

Dermal

Product: ATEmix: 3,066.43 mg/kg

Inhalation

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

Crystalline Silica (Quartz)/ Silica Sand

LC 50: > 5.0 mg/l

Titanium dioxide LC 50 (Rat): 3.43 mg/l

Cellulose LC 50 (Rabbit): 20.1 mg/l

Aluminum oxide LC 50 (Rat): 7.6 mg/l

Clay LC 50 (Rat): > 5 mg/l

Repeated dose toxicity

Product: No data available.



Revision Date: 11/11/2022

Skin Corrosion/Irritation

Product: No data available.

Specified substance(s):

Calcium carbonate in vivo (Rabbit): Not irritant, 24 - 72 h

Barium sulfate validated "in vitro" test method Not irritant

Propylene glycol in vivo (Rabbit): Not irritant, 24 - 72 h

Titanium dioxide in vivo (Rabbit): Not irritant, 24 h

Magnesite In vitro (Human, in vitro reconstituted epidermis model): not corrosive, 60

min

Aluminum oxide in vivo (Rabbit): Not irritant, 24 - 72 h

Serious Eye Damage/Eye Irritation

Product: No data available.

Specified substance(s):

Calcium carbonate Rabbit, 24 - 72 hrs: Not irritant

Barium sulfate Rabbit, 24 - 72 hrs: Not irritant

Titanium dioxide Rabbit, 24 - 72 hrs: Not irritant

Magnesite Reconstituted Corneal Epithelium model, 10 min: Not irritant

Aluminum oxide Rabbit, 24 hrs: Not irritant

Respiratory or Skin Sensitization

Product: No data available.

Carcinogenicity

Product: No data available.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Crystalline Silica

(Quartz)/ Silica

Sand

Overall evaluation: Carcinogenic to humans.

Titanium dioxide Overall evaluation: Possibly carcinogenic to humans.

US. National Toxicology Program (NTP) Report on Carcinogens:

Crystalline Silica Known To Be Human Carcinogen.

(Quartz)/ Silica

Sand



Revision Date: 11/11/2022

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended:

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro

No data available. Product:

In vivo

Product: No data available.

Reproductive toxicity

Product: No data available.

Specific Target Organ Toxicity - Single Exposure

No data available. Product:

Specific Target Organ Toxicity - Repeated Exposure

No data available. Product:

Aspiration Hazard

Product: No data available.

Constituents of this product may include crystalline silica which, if in Other effects:

inhalable form, may cause silicosis, a form of progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group I carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline silica is also listed by the NTP as a known human carcinogen. Constituents may also contain asbestiform or non-asbestiform tremolite or other silicates as impurities, and above de minimis exposure to these impurities in inhalable form may be carcinogenic

or cause other serious lung problems.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Barium sulfate LC 50 (Danio rerio, 96 h): > 3.5 mg/l Experimental result, Key study

Propylene glycol LC 50 (Oncorhynchus mykiss, 96 h): 40,613 mg/l Experimental result, Key

13/19



Revision Date: 11/11/2022

study

Titanium dioxide LC 50 (Pimephales promelas, 96 h): 8.2 mg/l Read-across from supporting

substance (structural analogue or surrogate), Supporting study

Magnesite LC 50 (Pimephales promelas, 96 h): 2,120 mg/l Read-across from

supporting substance (structural analogue or surrogate), Key study

Aluminum oxide LC 50 (Pimephales promelas, 96 h): 1.16 mg/l Experimental result, Weight

of Evidence study

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Barium sulfate LC 50 (Daphnia magna, 48 h): 14,500 µg/l experimental result Experimental

result, Key study

Propylene glycol LC 50 (Ceriodaphnia dubia, 48 h): 18,340 mg/l experimental result

Experimental result, Key study

Titanium dioxide LC 50 (Daphnia magna, 48 h): > 100 mg/l experimental result Experimental

result, Weight of Evidence study

Magnesite LC 50 (Daphnia magna, 48 h): 140 mg/l read-across from supporting

substance (structural analogue or surrogate) Read-across from supporting

substance (structural analogue or surrogate), Key study

Aluminum oxide EC 50 (Ceriodaphnia dubia, 48 h): 1.5 mg/l experimental result Experimental

result, Weight of Evidence study

Chronic hazards to the aquatic environment:

Fish

Product: No data available.

Specified substance(s):

Propylene glycol NOAEL (Pimephales promelas): 11,530 mg/l experimental result

Experimental result, Not specified

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Propylene glycol NOAEL (Ceriodaphnia sp.): 13,020 mg/l experimental result Experimental

result, Key study

Titanium dioxide NOAEL (Daphnia magna): 100 mg/l experimental result Experimental result,

Supporting study

Aluminum oxide NOAEL (Daphnia magna): 1.89 mg/l experimental result Experimental result,

Weight of Evidence study

Toxicity to Aquatic Plants

Product: No data available.



Revision Date: 11/11/2022

Persistence and Degradability

Biodegradation

Product: No data available.

Specified substance(s):

Propylene glycol 98.3 % (28 d) Detected in water. Experimental result, Key study

BOD/COD Ratio

Product: No data available.

Bioaccumulative potential

Bioconcentration Factor (BCF)

Product: No data available.

Specified substance(s):

Propylene glycol Bioconcentration Factor (BCF): 0.09 Aquatic sediment Estimated by

calculation, Supporting study

Partition Coefficient n-octanol / water (log Kow)

Product: No data available.

Specified substance(s):

Propylene glycol Log Kow: -0.92

Log Kow: -1.41 - -0.3 20 °C No Other, Supporting study

Mobility in soil: No data available.

Other adverse effects: Harmful to aquatic organisms.

13. Disposal considerations

Disposal methods: Dispose of waste at an appropriate treatment and disposal facility in

accordance with applicable laws and regulations, and product

characteristics at time of disposal.

Contaminated Packaging: No data available.

14. Transport information

TDG:

Not Regulated

CFR / DOT:

Not Regulated



Revision Date: 11/11/2022

IMDG:

Not Regulated

15. Regulatory information

US Federal Regulations

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

US. Toxic Substances Control Act (TSCA) Section 5(a)(2) Final Significant New Use Rules (SNURs) (40 CFR 721, Subpt E)

None present or none present in regulated quantities.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050), as amended

Chemical IdentityOSHA hazard(s)FormaldehydeSkin irritation

Flammability

respiratory tract irritation

Cancer Acute toxicity Skin sensitization Respiratory sensitization

Eye irritation

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity Reportable quantity

Barium sulfate 1000 lbs. Ammonium hydroxide 1000 lbs. Formaldehyde 100 lbs.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Delayed (Chronic) Health Hazard

US. EPCRA (SARA Title III) Section 304 Extremely Hazardous Substances Reporting Quantities and the Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) Hazardous Substances

US. EPCRA (SARA Title III Section 313 Toxic Chemical Release Inventory (TRI) Reporting Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Chemical Identity Reportable quantity

Formaldehyde lbs

Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

US State Regulations

US. California Proposition 65



Revision Date: 11/11/2022

For more information go to www.P65Warnings.ca.gov.

International regulations

Montreal protocol

Not applicable

Stockholm convention

Not applicable

Rotterdam convention

Not applicable

Kyoto protocol Not applicable

VOC:

Regulatory VOC (less water and : 74 g/l

exempt solvent)

VOC Method 310 : 2.67 %



Revision Date: 11/11/2022

Inventory Status:

Australia AICS: One or more components in this

product are not listed on or exempt

from the Inventory.

Canada DSL Inventory List: All components in this product are

listed on or exempt from the

Inventory.

EINECS, ELINCS or NLP: One or more components in this

product are not listed on or exempt

from the Inventory.

Japan (ENCS) List: One or more components in this

product are not listed on or exempt

from the Inventory.

China Inv. Existing Chemical

Substances:

One or more components in this product are not listed on or exempt

from the Inventory.

Korea Existing Chemicals Inv. (KECI): One or more components in this

product are not listed on or exempt

from the Inventory.

Canada NDSL Inventory: One or more components in this

product are not listed on or exempt

from the Inventory.

Philippines PICCS: One or more components in this

product are not listed on or exempt

from the Inventory.

New Zealand Inventory of Chemicals: One or more components in this

product are not listed on or exempt

from the Inventory.

Japan ISHL Listing: One or more components in this

product are not listed on or exempt

from the Inventory.

Japan Pharmacopoeia Listing:

One or more components in this

product are not listed on or exempt

from the Inventory.

US TSCA Inventory: All components in this product are

listed on or exempt from the

Inventory.



Revision Date: 11/11/2022

16.Other information, including date of preparation or last revision

Revision Date: 11/11/2022

Version #: 3.1

Further Information: No data available.

Disclaimer: For Industrial Use Only. Keep out of Reach of Children. The hazard

information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including

the safe use of the product under every foreseeable condition.